



TECHNICAL SPECIFICATION OF PRODUCT

BOMBOLONE ROTOLABILE 923LT- TP 49 BAR
TONCYLINDER 923LT – TP 49 BAR



<p>DESCRIZIONE:</p> <p>Bombolone Ricaricabile per Gas Refrigeranti -Capacità 923 lt -Test pressione 49 Bar -Temperatura utilizzo : -25 / +50°C -Dimensione Bombola: ø 800mm x 2221 mm -Attacco Valvola OUT: W21.7 x 1/14” -Valvola Omeca con Valvola Sicurezza taratura 42 bar.</p>	<p>DESCRIPTION:</p> <p>Refillable Ton Cylinder for Refrigerant Gases -Capacity 923 lt -Pressure Test 49 Bar -Temperature of working : -25 / +50°C -Cylinder Dimension: ø 800mm x 2221 mm -Connection OUT Valve: W21.7 x 1/14” -Omeca Valve with Security Valve calibrated 42 bar.</p>
<p>CERTIFICAZIONE :</p> <p>CE-TPED 99/36EC - EN14208 π1370 RICARICABILE – Gas Class 2 2A-2F-2TC</p>	<p>CERTIFICATION:</p> <p>CE-TPED 99/36EC - EN14208 π1370 REFILLABLE - Gas Class 2 2A-2F-2TC</p>
<p>GAS REFRIGERANTI</p> <p>Questo tipo di Bombolone può contenere i seguenti gas refrigeranti:</p> <p>-R134a; R404a; R407c; R410a; R507; R125; R152a; NH3; R22; R409; R413a ecc..</p>	<p>REFRIGERANT GASES:</p> <p>This kind of Ton Cylinder can contain the following gases:</p> <p>-R134a; R404a; R407c; R410a; R507; R125; R152a; NH3; R22; R409; R413a exc..</p>